


21003796 - Tandem 30.100 SS316 Wire mesh tray L3m



Product data

Product code:	21003796
Brand:	Niedax Group
Series:	Gouda Wire Mesh
Type:	Tandem
EAN Code:	08719972000155
Technical description:	Tandem 30.100 SS316 Wire mesh tray L3m
ETIM class:	EC000853 - Mesh cable tray

Technical data

RAL-number:	-
Working length:	3000
Type of connector:	Other
Operating temperature:	-20 - 120
Diameter longitudinal wire:	3.9
Diameter transverse wire:	3.9
Width:	100
Model:	Without connector
Height:	30
Surface protection:	Other
Weight:	0.535
Material quality:	Stainless steel 316 (1.4401)
Length:	3000
Material:	Stainless steel
Integrated partition:	None

Usable cross section:	2634
Profile shape:	U-shape
Suitable for circuit integrity:	No
Load test type according to IEC 61537:	Type III
Possible support spacing:	- - -
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.0 m:	-
Safe working load according to IEC 61537 with support spacing 1.5 m:	120
Safe working load according to IEC 61537 with support spacing 2.5 m:	50
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-
Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-
Safe working load according to IEC 61537 with support spacing 2.0 m:	80
Safe working load according to IEC 61537 with support spacing 3.0 m:	-
Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 5.0 m:	-