


# 22002793 - Tandem 54.70 HDG Wire mesh tray L3m



## Product data

Product code:	22002793
Brand:	Niedax Group
Series:	Gouda Wire Mesh
Type:	Tandem
EAN Code:	08719972000476
Technical description:	Tandem 54.70 HDG Wire mesh tray L3m
ETIM class:	EC000853 - Mesh cable tray

## Technical data

Possible support spacing:	- - -
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.0 m:	-
Safe working load according to IEC 61537 with support spacing 1.5 m:	300
Safe working load according to IEC 61537 with support spacing 2.0 m:	200
Safe working load according to IEC 61537 with support spacing 3.0 m:	-
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-

Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Safe working load according to IEC 61537 with support spacing 2.5 m:	150
Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 5.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-
Width:	70
Model:	Without connector
Height:	54
Surface protection:	Hot-dip galvanised
Weight:	0.812
Material quality:	Other
Length:	3000
Material:	Steel
Integrated partition:	None
Usable cross section:	-
Profile shape:	U-shape
Suitable for circuit integrity:	No
Diameter longitudinal wire:	3.9
RAL-number:	-
Operating temperature:	-20 - 120
Working length:	3000
Diameter transverse wire:	3.9