


## **22010793 - Tandem 54.600 HDG Wire mesh tray L3m**



## **Product data**

| Product code:          | 22010793                             |
|------------------------|--------------------------------------|
| Brand:                 | Niedax Group                         |
| Series:                | Gouda Wire Mesh                      |
| Туре:                  | Tandem                               |
| EAN Code:              | 08719972000759                       |
| Technical description: | Tandem 54.600 HDG Wire mesh tray L3m |
| ETIM class:            | EC000853 - Mesh cable tray           |

## **Technical data**

| Width:                                 | 600                |
|--|--------------------|
| Model:                                 | Without connector  |
| Height:                                | 55                 |
| Surface protection:                    | Hot-dip galvanised |
| Weight:                                | 4.199              |
| Material quality:                      | Other              |
| Length:                                | 3000               |
| Material:                              | Steel              |
| Integrated partition:                  | None               |
| Usable cross section:                  | 30526              |
| Profile shape:                         | U-shape            |
| Suitable for circuit integrity:        | No                 |
| Load test type according to IEC 61537: | Type III           |
| Operating temperature:                 | -20 - 120          |
| Diameter longitudinal wire:            | 4.82               |



| RAL-number:   | -    |
|---|------|
| Working length:   | 3000 |
| Diameter transverse wire:   | 5.82 |
| Possible support spacing:   |      |
| Safe working load according to IEC 61537 with support spacing 1.0 m:  | -    |
| Safe working load according to IEC 61537 with support spacing 2.5 m:  | 400  |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -    |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -    |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -    |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -    |
| Safe working load according to IEC 61537 with support spacing 0.5 m:  | -    |
| Safe working load according to IEC 61537 with support spacing 1.5 m:  | 800  |
| Safe working load according to IEC 61537 with support spacing 2.0 m:  | 600  |
| Safe working load according to IEC 61537 with support spacing 3.0 m:  | -    |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -    |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -    |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -    |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -    |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -    |
|   |      |