


# 23009791 - Tandem 105.500 EV Wire mesh tray L3m



## Product data

Product code:	23009791
Brand:	Niedax Group
Series:	Gouda Wire Mesh
Type:	Tandem
EAN Code:	08719972001220
Technical description:	Tandem 105.500 EV Wire mesh tray L3m
ETIM class:	EC000853 - Mesh cable tray

## Technical data

Operating temperature:	-20 - 120
Diameter longitudinal wire:	4.82
RAL-number:	-
Working length:	3000
Diameter transverse wire:	5.82
Safe working load according to IEC 61537 with support spacing 2.0 m:	900
Safe working load according to IEC 61537 with support spacing 3.0 m:	-
Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 5.0 m:	-
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-

Safe working load according to IEC 61537 with support spacing 8.0 m:	-
Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Possible support spacing:	- - -
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.0 m:	-
Safe working load according to IEC 61537 with support spacing 1.5 m:	1200
Safe working load according to IEC 61537 with support spacing 2.5 m:	700
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-
Width:	500
Model:	Without connector
Height:	105
Surface protection:	Galvanic/electrolytic zinc plated
Weight:	3.817
Material quality:	Other
Length:	3000
Material:	Steel
Integrated partition:	None
Usable cross section:	50026
Profile shape:	U-shape
Suitable for circuit integrity:	No
Load test type according to IEC 61537:	Type III