

# 26023236 - SLB MKRG 30.200 SS316 Marine ladder L3m



## Product data

|                        |   |
|------------------------|---|
| Product code:          | 26023236                                |
| Brand:                 | Niedax Group                            |
| Series:                | Gouda Marine ladders                    |
| Type:                  | SLB                                     |
| EAN Code:              | 08719972003538                          |
| Technical description: | SLB MKRG 30.200 SS316 Marine ladder L3m |
| ETIM class:            | EC000854 - Cable ladder                 |

## Technical data

|   |       |
|---|-------|
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -     |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -     |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -     |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -     |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -     |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -     |
| Possible support spacing:   | - - 3 |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -     |

|   |                              |
|---|------------------------------|
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -                            |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -                            |
| Width:  | 200                          |
| Height:   | 30                           |
| RAL-number:   | -                            |
| Surface protection:   | Other                        |
| Weight:   | 3.1897                       |
| Type of rung:   | Flat profile                 |
| Side perforation:   | No                           |
| Material quality:   | Stainless steel 316 (1.4401) |
| Length:   | 3000                         |
| Material:   | Stainless steel              |
| Usable cross section:   | -                            |
| Type of side joist:   | Flat profile                 |
| Suitable for circuit integrity:                                       | No                           |
| Rung centre spacing:  | 250                          |
| Fixation rung:  | Welded                       |
| Operating temperature:  | -20 - 120                    |
| Working length:   | 3000                         |
| Vertical cable ladder:  | -                            |