

## 31047153 - Tray GP 28.300 HDG Cable tray L3m

## **Product data**

| Product code:          | 31047153                          |
|------------------------|-----------------------------------|
| Brand:                 | Niedax Group                      |
| Series:                | Gouda Cable duct                  |
| Туре:                  | Tray                              |
| EAN Code:              | 08719972008670                    |
| Technical description: | Tray GP 28.300 HDG Cable tray L3m |
| ETIM class:            | EC000047 - Cable tray             |

## **Technical data**

| Without connector 27 |
|----------------------|
| 27                   |
|                      |
| -                    |
| Hot-dip galvanised   |
| -                    |
| 1.5                  |
| Yes                  |
| Other                |
| 3000                 |
| Steel                |
| Yes                  |
| 7574                 |
| No                   |
| No                   |
| No                   |
| -                    |
| 300                  |
| 175                  |
|                      |



| Safe working load according to IEC 61537 with support spacing 3.0 m:  | 25        |
|---|-----------|
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -         |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -         |
| Possible support spacing:   | 3         |
| Safe working load according to IEC 61537 with support spacing 1.0 m:  | 450       |
| Safe working load according to IEC 61537 with support spacing 2.5 m:  | 80        |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -         |
| Type of connector:  | Screwed   |
| Operating temperature:  | -20 - 120 |
| Working length:   | 3000      |
|   |           |