

# 31062143 - Tray ZP 28.75 HDG Cable tray L3m

## Product data

|                        |                                  |
|------------------------|----------------------------------|
| Product code:          | 31062143                         |
| Brand:                 | Niedax Group                     |
| Series:                | Gouda Cable duct                 |
| Type:                  | Tray                             |
| EAN Code:              | 08719972008779                   |
| Technical description: | Tray ZP 28.75 HDG Cable tray L3m |
| ETIM class:            | EC000047 - Cable tray            |

## Technical data

|   |           |
|---|-----------|
| Type of connector:  | Screwed   |
| Operating temperature:  | -20 - 120 |
| Working length:   | 3000      |
| Possible support spacing:   | - - 3     |
| Safe working load according to IEC 61537 with support spacing 1.0 m:  | 450       |
| Safe working load according to IEC 61537 with support spacing 2.5 m:  | 80        |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -         |
| Safe working load according to IEC 61537 with support spacing 0.5 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 1.5 m:  | 300       |
| Safe working load according to IEC 61537 with support spacing 2.0 m:  | 175       |

|   |                    |
|---|--------------------|
| Safe working load according to IEC 61537 with support spacing 3.0 m:  | 25                 |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -                  |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -                  |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -                  |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -                  |
| Width:  | 75                 |
| Model:  | Without connector  |
| Height:   | 27                 |
| RAL-number:   | -                  |
| Surface protection:   | Hot-dip galvanised |
| Weight:   | -                  |
| Material thickness:   | 1.5                |
| Side perforation:   | No                 |
| Material quality:   | Other              |
| Length:   | 3000               |
| Material:   | Steel              |
| Bottom perforation:   | No                 |
| Usable cross section:   | 1836               |
| NATO-mounting holes:  | No                 |
| Suitable for circuit integrity:                                       | No                 |
| With cover:   | No                 |