

## 31067146 - Tray ZP 28.300 SS316 Cable tray L3m

## **Product data**

Product code:	31067146
Brand:	Niedax Group
Series:	Gouda Cable duct
Туре:	Тгау
EAN Code:	08719972009042
Technical description:	Tray ZP 28.300 SS316 Cable tray L3m
ETIM class:	EC000047 - Cable tray

## **Technical data**

Type of connector:	Screwed
Working length:	3000
Operating temperature:	-20 - 120
Safe working load according to IEC 61537 with support spacing 2.0 m:	175
Safe working load according to IEC 61537 with support spacing 3.0 m:	25
Safe working load according to IEC 61537 with support spacing 4.0 m:	-
Safe working load according to IEC 61537 with support spacing 6.0 m:	-
Safe working load according to IEC 61537 with support spacing 7.0 m:	-
Safe working load according to IEC 61537 with support spacing 8.0 m:	-
Safe working load according to IEC 61537 with support spacing 10.0 m:	-
Safe working load according to IEC 61537 with support spacing 9.0 m:	-
Possible support spacing:	3
Safe working load according to IEC 61537 with support spacing 0.5 m:	-
Safe working load according to IEC 61537 with support spacing 1.0 m:	450



Safe working load according to IEC 61537 with support spacing 1.5 m:	300
Safe working load according to IEC 61537 with support spacing 2.5 m:	80
Safe working load according to IEC 61537 with support spacing 5.0 m:	-
Safe working load according to IEC 61537 with support spacing 11.0 m:	-
Safe working load according to IEC 61537 with support spacing 12.0 m:	-
Width:	300
Model:	Without connector
Height:	27
RAL-number:	-
Surface protection:	Untreated
Weight:	
Material thickness:	1
Side perforation:	No
Material quality:	Stainless steel 316 (V4A)
Length:	3000
Material:	Stainless steel
Bottom perforation:	No
Usable cross section:	7748
NATO-mounting holes:	No
Suitable for circuit integrity:	No
With cover:	No