

## 31086152 - Tray GPR 28.250 PG Cable tray L3m



## **Product data**

| Product code:          | 31086152                          |
|------------------------|-----------------------------------|
| Brand:                 | Niedax Group                      |
| Series:                | Gouda Cable duct                  |
| Туре:                  | Тгау                              |
| EAN Code:              | 08719972009318                    |
| Technical description: | Tray GPR 28.250 PG Cable tray L3m |
| ETIM class:            | EC000047 - Cable tray             |

## **Technical data**

| Possible support spacing:   | 3   |
|---|-----|
| Safe working load according to IEC 61537 with support spacing 0.5 m:    | -   |
| Safe working load according to IEC 61537 with support spacing 1.0 m:    | 600 |
| Safe working load according to IEC 61537 with support spacing 1.5 m:    | 410 |
| Safe working load according to IEC 61537 with support spacing 2.5 m:    | 160 |
| Safe working load according to IEC 61537 with support spacing 3.0 m:    | 50  |
| Safe working load according to IEC 61537 with support spacing 6.0 m:    | -   |
| Safe working load according to IEC 61537 with support spacing 8.0 m:    | -   |
| Safe working load according to IEC 61537<br>with support spacing 9.0 m: | -   |



| Safe working load according to IEC 61537 with support spacing 11.0 m: | -                       |
|---|-------------------------|
| Safe working load according to IEC 61537 with support spacing 2.0 m:  | 250                     |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -                       |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -                       |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -                       |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -                       |
| Safe working load according to IEC 61537 with support spacing 12.0 m: |                         |
| Width:  | 250                     |
| Model:  | Without connector       |
| Height:   | 28                      |
| RAL-number:   | -                       |
| Surface protection:   | Continuously galvanised |
| Weight:   | -                       |
| Material thickness:   | 1                       |
| Side perforation:   | Yes                     |
| Material quality:   | Other                   |
| Length:   | 3000                    |
| Material:   | Steel                   |
| Bottom perforation:   | Yes                     |
| Usable cross section:   | 5704                    |
| NATO-mounting holes:  | No                      |
| Suitable for circuit integrity:                                       | No                      |
| With cover:   | No                      |
| Type of connector:  | Screwed                 |
| Operating temperature:  | -20 - 120               |
| Working length:   | 3000                    |
|   |                         |