

# 31106144 - Tray ZPR 28.250 SS304 Cable tray L3m



## Product data

|                        |                                      |
|------------------------|--------------------------------------|
| Product code:          | 31106144                             |
| Brand:                 | Niedax Group                         |
| Series:                | Gouda Cable duct                     |
| Type:                  | Tray                                 |
| EAN Code:              | 08719972009684                       |
| Technical description: | Tray ZPR 28.250 SS304 Cable tray L3m |
| ETIM class:            | EC000047 - Cable tray                |

## Technical data

|                                 |                           |
|---------------------------------|---------------------------|
| Width:                          | 250                       |
| Model:                          | Without connector         |
| Height:                         | 28                        |
| RAL-number:                     | -                         |
| Surface protection:             | Untreated                 |
| Weight:                         | -                         |
| Material thickness:             | 1                         |
| Side perforation:               | No                        |
| Material quality:               | Stainless steel 304 (V2A) |
| Length:                         | 3000                      |
| Material:                       | Stainless steel           |
| Bottom perforation:             | No                        |
| Usable cross section:           | 5704                      |
| NATO-mounting holes:            | No                        |
| Suitable for circuit integrity: | No                        |

|   |           |
|---|-----------|
| With cover:   | No        |
| Working length:   | 3000      |
| Type of connector:  | Screwed   |
| Operating temperature:  | -20 - 120 |
| Safe working load according to IEC 61537 with support spacing 2.0 m:  | 250       |
| Safe working load according to IEC 61537 with support spacing 4.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 5.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 6.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 8.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 9.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | -         |
| Possible support spacing:   | - - 3     |
| Safe working load according to IEC 61537 with support spacing 0.5 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 1.0 m:  | 600       |
| Safe working load according to IEC 61537 with support spacing 1.5 m:  | 410       |
| Safe working load according to IEC 61537 with support spacing 2.5 m:  | 160       |
| Safe working load according to IEC 61537 with support spacing 3.0 m:  | 50        |
| Safe working load according to IEC 61537 with support spacing 7.0 m:  | -         |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | -         |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | -         |