

71002235 - Crafty MF 100.200 AL Cable Ladder c.t.c.300 L3m



Product data

| Product code: | 71002235 |
|------------------------|---|
| Brand: | Niedax Group |
| Series: | Gouda Cable ladder |
| Type: | Crafty |
| EAN Code: | 08719972115859 |
| Technical description: | Crafty MF 100.200 AL Cable Ladder c.t.c.300 L3m |
| ETIM class: | EC000854 - Cable ladder |

Technical data

| Colour: | Aluminium |
|---------------------------------|--------------------|
| Width: | 200 |
| Height: | 100 |
| RAL-number: | |
| Surface protection: | Other |
| Weight: | |
| Type of rung: | Perforated profile |
| Side perforation: | Yes |
| Material quality: | Other |
| Length: | 3000 |
| Material: | Aluminium |
| Usable cross section: | |
| Type of side joist: | Profile (open) |
| Suitable for circuit integrity: | No |



| | - Codda Holland |
|---|-----------------|
| Rung centre spacing: | 300 |
| Fixation rung: | Welded |
| Possible support spacing: | 4.5 |
| Safe working load according to IEC 61537 with support spacing 0.5 m: | - |
| Safe working load according to IEC 61537 with support spacing 1.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 1.5 m: | - |
| Safe working load according to IEC 61537 with support spacing 2.5 m: | - |
| Safe working load according to IEC 61537 with support spacing 6.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 7.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 8.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 9.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 2.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 3.0 m: | 2200 |
| Safe working load according to IEC 61537 with support spacing 4.0 m: | 650 |
| Safe working load according to IEC 61537 with support spacing 5.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 10.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 11.0 m: | - |
| Safe working load according to IEC 61537 with support spacing 12.0 m: | - |
| Working length: | 3000 |
| Vertical cable ladder: | - |
| Operating temperature: | -20 - 120 |
| | |